

## ID BOX - ID3 Desktop series

*e-Document verification without movement*



- Dedicated to ePassports and all identity documents
- Scans MRZ and reads RFID chip without movement
- Supports ICAO & national eID standards
- Fast reading
- Reduced footprint
- USB powered
- Automatic detection

## Product Range

	ID BOX 111	ID BOX 121	ID BOX 141	ID BOX 142	ID BOX 143	ID BOX 144	ID BOX 151	ID BOX 152
MRZ scanner	✓	✓	✓	✓	✓	✓	✓	✓
Contactless reader		✓	✓	✓	✓	✓	✓	✓
Contact reader			✓ (2 units)	✓	✓		✓ (2 units)	✓
SAM reader							✓	✓
1D/2D scanner					✓	✓		
Fingerprint sensor				✓		✓		✓

ID BOX 142



ID BOX 121



ID BOX 151



## Features

### General

- Dimensions 140 x 90 x 105 mm for ID BOX 111 and 121  
140 x 90 x 115 mm for ID BOX 143 & 151  
140 x 120 x 115 mm for ID BOX 142 & 152
- Temperature In operation: 0°C to +50°C  
Storage: -40°C to +80°C
- Communication USB 2.0 full speed (12 Mbps)
- Host operating systems Windows, MacOS, Linux, Android

### MRZ scanner

- MRZ Lines 1 line: IDL, CAN, ...  
2 lines: ID2 cards, ePP  
3 lines: eID
- Font Type OCR B

### Contactless reader

- Supported protocols ISO 14443 Part 1 to 4, type A/B – T=CL and Mifare  
All Mifare products: Ultralight, 1K, 4K, Plus, DESFire EV1,  
Smart MX,...
- Speed Baudrate up to 848 kbps
- Number of antennas 2
- Communication CCID compliant (Windows, MacOS, Linux)  
Custom CCID library (Android)  
PC/SC 2.01 compliant (Windows, MacOS, Linux)  
PC/SC .net wrapper (Windows)
- Firmware Support for RF configuration  
Path-through command to reach protocol lower layer  
Field upgradable

### Contact card readers

- Supported protocols ISO 7816 – T=0 and T=1  
EMV 2011 4.3 level 1  
Memory cards thanks to M-Card API  
5V, 3V, 1.8V, ISO 7816 Class A/B/C
- Speed Baudrate up to 600 kbps  
TA1=97 supported  
Clock: 5 Mhz (ISO 7186) – Up to 12 MHz
- Communication CCID compliant (Windows, MacOS, Linux)  
Custom CCID library (Android)  
PC/SC 2.01 compliant (Windows, MacOS, Linux)  
PC/SC .net wrapper (Windows)

### Fingerprint sensor

- Image quality Standard FBI PIV / FBI Mobile  
ID FAP 20
- Sensor type Optical
- Resolution 500 ppi

### 1D/2D barcode scanner

- Supported media Paper and screen
- Supported codes 2D : QR, PDF417, LPDF417, Data Matrix, Maxicode, Aztec,  
Hanxin, etc  
1D : EAN, UPC, Code 39, Code 93, Code 128, Codabar,  
Interleaved 2 of 5, ITF-6, etc

## ELYCTIS sas

91 rue Benjamin Franklin – 84120 Pertuis – FRANCE  
Tel. +33 6 27 71 37 68

[contact@elyctis.com](mailto:contact@elyctis.com) - [www.elyctis.com](http://www.elyctis.com)

Siret 508 994 449 00033 – VAT number FR47 508 994 449

## ELYCTIS HK Limited

D2 2/F Mai Wah Ind. Bldg. – 1-7 Wah Sing St. Kwai Chung NT –  
HONG KONG

Tel. +852 91 08 78 58

[contact\\_hongkong@elyctis.com](mailto:contact_hongkong@elyctis.com)